



Description	EBC22
	EBC22EU01/EBC22EU02
Height x width x depth	204,3 x 239,5 x 77,2 mm
Weight	1,62 kg
IP-rating / material	IP54 / ABS PA758
Voltage	230 V AC $\pm 10\%$, 50 Hz $\pm 1\%$
Max power consumption	475 W
Fuse	T4A
Temperature	-20 °C to 60 °C
Monitoring range	-500 Pa to +500 Pa
Sensor	XTP 150G
Dimension (w x h x d)	115 x 90 x 55 mm
Operating temperature	0 °C to +70 °C
Monitoring range	0 Pa to +150 Pa
Max distance between EBC20 and XTP sensor	100 m
IP-rating	IP54
mA	75
EBC22 Inputs	
Digital inputs (D11 & D12)	18 to 230 V AC/DC
Pressure sensor (XTP) input	0 to 10 V DC, 20 mA
Pressure switch (PDS) input	24 V DC, 20 mA
Temperature sensor PT1000	Accessory number: 1100755
EBC22 Outputs	
Digital relay outputs (DO1 & DO2)	250 V AC, 5A
Motor regulator	-3 %, 3 A, AC3
Motor start/stop relay	250 V AC, 8A
Control signal 0-10 VDC	20 mA
24 V DC power supply	100 mA
Alarm output relay	250 V AC, 8A
Approval	CE mark, Kiwa Gastec

The EBC22 can be used with all **exodraft** chimney fan types.

EBC22EU01 Control for indoor installation.

EBC22EU02 Control for outdoor installation.

Hekon art. : EXH-EBC22